

ОБСАДНЫЕ ТРУБЫ стандарт API 5 CT

	Удельный вес, кг/м	Наружный диаметр		Толщина стенки		Тип высадки			
		мм	дюйм	мм	дюйм	J55	N80	L80	P110
4 1/2"	15.63	114.30	4.500	5.69	0.224	PSB	-	-	-
	17.26	114.30	4.500	6.35	0.250	PSLB	PLB	PLB	PLB
	20.09	114.30	4.500	7.37	0.290	-	PLB	PLB	PLB
	22.47	114.30	4.500	8.56	0.337	-	-	-	PLB
5"	17.11	127.00	5.000	5.59	0.220	PS	-	-	-
	19.35	127.00	5.000	6.43	0.253	PSLB	-	-	-
	22.32	127.00	5.000	7.52	0.296	PSLB	PLB	PLB	PLB
	26.79	127.00	5.000	9.19	0.362	-	PLB	PLB	PLB
	31.85	127.00	5.000	11.10	0.437	-	PLB	PLB	PLB
	34.53	127.00	5.000	12.14	0.478	-	PLB	PLB	PLB
5 1/2"	20.83	139.70	5.500	6.20	0.244	PS	-	-	-
	23.07	139.70	5.500	6.98	0.275	PSLB	-	-	-
	25.30	139.70	5.500	7.72	0.304	PSLB	PLB	PLB	PLB
	29.76	139.70	5.500	9.17	0.361	-	PLB	PLB	PLB
	34.23	139.70	5.500	10.54	0.415	-	PLB	PLB	PLB
	39.88	139.70	5.500	12.70	0.500	-	-	-	-
6 5/8"	29.76	168.28	6.625	7.32	0.288	PSLB	-	-	-
	35.72	168.28	6.625	8.94	0.352	PSLB	PLB	PLB	PLB
	41.67	168.28	6.625	10.59	0.417	-	PLB	PLB	PLB
	47.62	168.28	6.625	12.06	0.475	-	PLB	PLB	PLB
7"	25.30	177.80	7.000	5.87	0.231	-	-	-	-
	29.76	177.80	7.000	6.91	0.272	PS	-	-	-
	34.23	177.80	7.000	8.05	0.317	PSLB	PLB	PLB	-
	38.69	177.80	7.000	9.19	0.362	PSLB	PLB	PLB	PLB
	43.16	177.80	7.000	10.36	0.408	-	PLB	PLB	PLB
	47.62	177.80	7.000	11.51	0.453	-	PLB	PLB	PLB
	52.09	177.80	7.000	12.65	0.498	-	PLB	PLB	PLB
7 5/8"	35.72	193.68	7.625	7.62	0.300	-	-	-	-
	39.29	193.68	7.625	8.33	0.328	PSLB	PLB	PLB	-
	44.20	193.68	7.625	9.53	0.375	-	PLB	PLB	PLB
	50.15	193.68	7.625	10.92	0.430	-	PLB	PLB	PLB
	58.04	193.68	7.625	12.70	0.500	-	PLB	PLB	PLB
8 5/8"	35.72	219.08	8.625	6.71	0.264	PS	-	-	-
	41.67	219.08	8.625	7.72	0.304	-	-	-	-
	47.62	219.08	8.625	8.94	0.352	PLB	-	-	-
	53.57	219.08	8.625	10.16	0.400	PLB	PLB	PLB	-
	59.53	219.08	8.625	11.43	0.450	-	PLB	PLB	PLB
	65.48	219.08	8.625	12.70	0.500	-	PLB	PLB	PLB
9 5/8"	48.07	244.48	9.625	7.92	0.312	-	-	-	-
	53.57	244.48	9.625	8.94	0.352	PSLB	-	-	-
	59.53	244.48	9.625	10.03	0.395	PSLB	PLB	PLB	-
	64.73	244.48	9.625	11.05	0.435	-	PLB	PLB	PLB
	69.94	244.48	9.625	11.99	0.472	-	PLB	PLB	PLB
10 3/4"	48.74	273.05	10.75	7.09	0.279	-	-	-	-
	60.27	273.05	10.75	8.89	0.350	PSB	-	-	-
	67.71	273.05	10.75	10.16	0.400	PSB	-	-	-
	75.90	273.05	10.75	11.43	0.450	PSB	PSB	PSB	PSB
	82.59	273.05	10.75	12.57	0.495	-	PSB	PSB	PSB
11 3/4"	62.50	298.45	11.75	8.46	0.333	-	-	-	-
	69.94	298.45	11.75	9.53	0.375	PSB	-	-	-
	80.36	298.45	11.75	11.05	0.435	PSB	-	-	-
	89.29	298.45	11.75	12.42	0.489	PSB	PSB	PSB	PSB
13 3/8"	71.43	339.73	13.375	8.38	0.330	-	-	-	-
	81.10	339.73	13.375	9.65	0.380	PSB	-	-	-

	90.78	339.73	13.375	10.92	0.430	PSB	-	-	-
	101.19	339.73	13.375	12.19	0.480	PSB	PSB	PSB	PSB
	107.15	339.73	13.375	13.06	0.514	-	PSB	PSB	PSB

P – без резьбы и высадки

S – короткая резьба

L – длинная резьба

B – резьба типа Buttress.

Все резьбовые соединения защищены протекторами.